

# Pipelines

Sample	Size	Connect	用途 Use
N1	1.5" (ø38)	卡箍Clamp	物料口Material outlet port
N2	1.25" (ø32)	卡箍Clamp	反冲洗口Backwash port
N3	1.25" (ø32)	卡箍Clamp	洗涤口Cleaning port
N4	1.25" (ø32)	卡箍Clamp	回流口Backflow port
N5	1.25" (ø32)	卡箍Clamp	洗槽水进口Inlet of spent grain water
N6	ø10		温度计盲管Thermometer blind tube
N7	ø350		玻璃人孔Glass manhole
N8	440×330		出槽门Spent grain door
N9	ø19		电机穿线口Motor Thread crossing port
N10	ø80		视灯 (带电源) LED light (with power supply)
N11	ø25	卡箍Clamp	液位计接口Level indicator interface
N12	ø25	卡箍Clamp	液位计接口Level indicator interface
N13	ø25	卡箍Clamp	平衡口Buffer port

## 技术要求

1. 总容积: 650L, 有效容积: 500L; Total volume: 650L, effective volume: 500L;
2. 封头内外抛光至 $0.6\mu\text{m}$ , 其余均做好板面保护, 焊缝处抛40mm细砂光带, 支腿与外包下锥之间满焊;
3. 焊接采用氩弧焊, 具体要求参见《焊接作业指导书图集》;
4. 制作完毕, 筒体盛水试漏, 机械部分试运转2小时, 确保运转平稳, 无噪音, 无其他异常情况;

